# CHASBKARAN SAHELE ARAS CO.

# MATERIAL SAFETY DATA SHEETS

# FINAL FOAM

# SECTION 1: IDENTIFICATIONS OF THE SUBSTANCE /MIXTURE AND OF THE COMPANY/UNDERTAKING

# 1.1. Product identifier

Product form : MIXTURE

Trade name : FINAL FOAM 750 ML- 600 GR

Type of product : AEROSOL

Product group : TRADE PRODUCT

# 1.2. Relevant identified uses of the substance or mixture and uses discouraged

Intended use: Silicone sealant.

# 1.3. Details of the supplier providing the safety data sheet

Head office: Chasbkaran Sahel Aras Co. 4th Floor, No.2, Mahan Bldg, Mojahedi Alley, Tavanir Blvd,

Valiasr, Tabriz, Iran

Phone: +98 (41) 4196

info@csa-team.com www.chasbkaran.com

# 1.4. Emergency telephone number

In Case Of Emergency: +98 (41) 4196

# SECTION 2: HAZARDS IDENTIFICATION

Specific target organ toxicity — Repeated exposure

### 2.1. Classification of the substance or mixture

# Classification according to Regulation (EC) No. 1272/2008 [CLP]M

H222; H229	On basis of test data
H332	Calculation method
H315	Calculation method
H319	Calculation method
H334	Calculation method
H317	Calculation method
H351	Calculation method
H335	Calculation method
	H332 H315 H319 H334 H317

H373

Calculation method



### 2.2. Label elements

# Labelling according to Regulation (EC) No. 1272/2008 [CLP]

Hazard pictograms (CLP)







: Danger

GHS07

: Isocyanic acid, polymethylenepolyphenylene

Signal word (CLP)

Hazardous ingredients

ester.

Hazard statements (CLP)

heated.

H315 - Causes skin irritation.

H317 - May cause an allergic skin reaction.

H229 - Pressurized container: May burst if

H319 - Causes serious eye irritation.

: H222 - Extremely flammable aerosol.

H332 - Harmful if inhaled.

H334 - May cause allergy or asthma symptoms or

breathing difficulties if inhaled.

H335 - May cause respiratory irritation.

H351 - Suspected of causing cancer.

H373 - May cause damage to organs through

prolonged or repeated exposure.

: P102 - Keep out of reach of children.

P210 - Keep away from heat, hot surfaces, sparks,

open flames and other ignition sources. No

smoking.

P211 - Do not spray on an open flame or other

ignition source.

P251 - Do not pierce or burn, even after use.

P280 - Wear eye protection, protective clothing,

protective gloves, face protection.

P284 - [In case of inadequate ventilation] wear

respiratory protection.

P302+P352 - IF ON SKIN: Wash with plenty of

Precautionary statements (CLP)

Chasbkaran Sahel Aras Co. 4th Floor, No.2, Mahan Bldg., Mojahedi Alley, Tavanir Blvd, Valiasr, Tabriz, Iran.

Tel: +98 (413) 328 41 18-20 Fax: +98 (413) 328 41 00 www.chasbkaran.com



water.

P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do.

P342+P311 - If experiencing respiratory symptoms: Call a doctor, a POISON CENTER.

P410+P412 - Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.

P501 - Dispose of contents/container to hazardous or special waste collection point, in accordance with local regional, national and/or international regulation.

P261 - Avoid breathing gas, spray, vapors.

: EUH204 - Contains isocyanates. May produce an allergic reaction.

**EUH-statements** 

# SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

### 3.1. Mixture

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
Isocyanic acid, polymethylenepolyphenylene ester	(CAS No) 9016-87-9 (REACH-no) 01-2119457014-47	20 - 35	Acute Tox. 4 (Inhalation), H332 Skin Irrit. 2, H315 Eye Irrit. 2, H319 Resp. Sens. 1, H334 Skin Sens. 1, H317 Carc. 2, H351 STOT SE 3, H335 STOT RE 2, H373
isobutane (Note C) (Note U)	(CAS No) 75-28-5 (EC no) 200-857-2 (EC index no) 601-004-00-0 (REACH-no) 01-2119485395-27	2.5 - 10	Flam. Gas 1, H220
dimethyl ether	(CAS No) 115-10-6	2.5 - 10	Flam. Gas 1, H220
(Note U)	(EC no) 204-065-8 (EC index no) 603-019-00-8 (REACH-no) 01-2119472128-37		Press. Gas



propane (Note U)	(CAS No) 74-98-6	2.5 - 10	Flam. Gas 1,
	(EC no) 200-827-9		H220
	(EC index no) 601-003-00-5		Press. Gas
	(REACH-no) 01-2119486944-21		

Note C: Some organic substances may be marketed either in a specific isomeric form or as a mixture of several isomers. In this case the supplier must state on the label whether the substance is a specific isomer or a mixture of isomers.

Note U: When put on the market gases have to be classified as 'Gases under pressure', in one of the groups compressed gas, liquefied gas, refrigerated liquefied gas or dissolved gas. The group depends on the physical state in which the gas is packaged and therefore has to be assigned case by case.

# **SECTION 4: FIRST AID MEASURES**

# 4.1. Description of first aid measures:

: IF exposed or concerned: Get medical advice/attention. Call a poison center or a doctor if you feel unwell.

First-aid measures after inhalation : Remove person to fresh air and keep comfortable for breathing. Call a poison center or a doctor if

you feel unwell.

First-aid measures after skin contact : Wash skin with plenty of water. Take off

contaminated clothing. If skin irritation or rash

occurs: Get medical advice/attention.

First-aid measures after eye contact : Rinse cautiously with water for several minutes.

Remove contact lenses, if present and easy to do.

Continue rinsing. If eye irritation persists: Get

medical advice/attention.

First-aid measures after ingestion : Call a poison center or a doctor if you feel

unwell.

## 4.2. Most important symptoms and effects, both acute and delayed

Symptoms/injuries after inhalation : May cause respiratory irritation. May cause allergy

or asthma symptoms or breathing difficulties if

inhaled.

Symptoms/injuries after skin contact : Irritation. May cause an allergic skin reaction.

Symptoms/injuries after eye contact : Eye irritation.



# SECTION 5: FIREFIGHTING MEASURES

# 5.1. Extinguishing media

Suitable extinguishing media : Water spray. Dry powder. Foam.

5.2. Special hazards arising from the substance or mixture

Fire hazard : Extremely flammable aerosol.

Explosion hazard : Pressurized container: May burst if heated.

Hazardous decomposition products : Toxic fumes may be released.

in case of fire

5.3. Advice for firefighters

Protection during firefighting : Do not attempt to take action without suitable

protective equipment. Self-contained breathing

apparatus. Complete protective clothing.

# **SECTION 6: HANDLING AND STORAGE**

# 6.1. Precautions for safe handling

Precautions for safe handling : Keep away from heat, hot surfaces, sparks, open

flames and other ignition sources. No smoking. Do

not spray on an open flame or other ignition source.

Pressurized container: Do not pierce or burn, even

after use. Obtain special instructions before use. Do

not handle until all safety precautions have been

read and understood. Wear personal protective

equipment. Do not breathe dust/ fume/gas/mist

vapors/spray. Use only outdoors or in

a well-ventilated area. Avoid contact with skin and

eyes.

Hygiene measures : Wash contaminated clothing before reuse.

Contaminated work clothing should not be allowed

out of the workplace.

Do not eat, drink or smoke when using this product.

Always wash hands after handling the product.

# SECTION 7: EXPOSURE CONTROLS/PERSONAL PROTECTION

### 7.1. Exposure controls

Appropriate engineering controls : Ensure good ventilation of the work station.

Hand protection : Protective gloves.

Chasbkaran Sahel Aras Co. 4th Floor, No.2, Mahan Bldg., Mojahedi Alley, Tavanir Blvd, Valiasr, Tabriz, Iran. Tel: +98 (413) 328 41 18-20 Fax: +98 (413) 328 41 00 www.chasbkaran.com



Eye protection : Safety glasses.

Skin and body protection : Wear suitable protective clothing.

Respiratory protection : Wear respiratory protection.

Environmental exposure controls : Avoid release to the environment.

# SECTION 8: PHYSICAL AND CHEMICAL PROPERTIES

### 8.1. Information on basic physical and chemical properties

Physical state Gas

Appearance Liquid under pressure

Color

Odor Characteristic

Flash point 0 °C

Flammability (solid, gas) Extremely flammable aerosol

Vapor pressure 5 bar

Density 19 - 25 kg/m<sup>3</sup>

# **SECTION 9: STABILITY AND REACTIVITY**

### 9.1. Reactivity

Extremely flammable aerosol. Pressurized container: May burst if heated.

# 9.2. Chemical stability

Stable under normal conditions.

# 9.3. Possibility of hazardous reactions

No dangerous reactions known under normal conditions of use.

### 9.4. Conditions to avoid

Avoid contact with hot surfaces. Heat. No flames, no sparks. Eliminate all sources of ignition.

## 9.5. Incompatible materials

No additional information available.

# 9.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced.

# SECTION 10: TOXICOLOGICAL INFORMATION

### 10.1. Information on toxicological effects

Acute toxicity : Inhalation gas Harmful if inhaled.

ATE CLP (gases) :12857.143 ppmv/4h

Skin corrosion/irritation : Causes skin irritation.

Serious eye damage/irritation : Causes serious eye irritation

Chasbkaran Sahel Aras Co. 4th Floor, No.2, Mahan Bldg., Mojahedi Alley, Tavanir Blvd, Valiasr, Tabriz, Iran. Tel: +98 (413) 328 41 18-20 Fax: +98 (413) 328 41 00 www.chasbkaran.com



Respiratory or skin sensitisation : May cause allergy or asthma symptoms or breathing

difficulties if inhaled. May cause an allergic skin reaction.

Carcinogenicity : Suspected of causing cancer.

# SECTION 11: ECOLOGICAL INFORMATION

11.1. Toxicity

Ecology - general : The product is not considered harmful to aquatic organisms

to cause long-term adverse effects in the environment.

# SECTION 12: DISPOSAL CONSIDERATIONS

12.1. Waste treatment methods

Waste treatment methods : Dispose of contents/container in accordance with licensed

collector's sorting instructions.

# SECTION 13: ACCIDENTAL RELEASE MEASURES

SPILL CLEAN UP METHODS: When dealing with a spillage, please consult the section relating to suitable protective measures. Wear necessary protective equipment. Stop leak if possible without risk. Flush with plenty of water to clean spillage area. Do not contaminate water sources or sewer.

# **SECTION 14: TRANSPORT INFORMATION**

**PROPER SHIPPING NAME: AEROSOLS** 

**ENVIRONMENTALLY HAZARDOUS No.** 

SUBSTANCE/MARINE POLLUTANT

UN NO. ROAD 1950

ADR CLASS NO. 2

ADR CLASS Class 2: Gases

ADR PACK GROUP N/A

TUNNEL RESTRICTION CODE (D)

ADR LABEL NO. 2.1

UN NO. SEA 1950

**IMDG CLASS 2.1** 

IMDG PACK GR. N/A

EMS F-D, S-U

UN NO. AIR 1950

AIR CLASS 2.1

AIR PACK GR. N/A

# CHASBKARAN SAHELE ARAS CO.

# MATERIAL SAFETY DATA SHEETS

# SECTION 15: REGULATORY INFORMATION

### **LABELLING**

Harmful

Extremely Flammable

### **EU DIRECTIVES**

Dangerous Substance Directive 67/548/EEC. Dangerous Preparations Directive 1999/45/EC. System of specific information relating to Dangerous Preparations. 2001/58/EC. Commission Directive 2000/39/EC of 8 June 2000 establishing a first list of indicative occupational exposure limit values in implementation of Council Directive 98/24/EC on the protection of the health and safety of workers from the risks related to chemical agents at work. Regulation (EC) No 1907/2006 of the European Parliament and of the Council of 18 December 2006 concerning the Registration, Evaluation, Authorization and Restriction of Chemicals (REACH), establishing a European Chemicals Agency, amending Directive 1999/45/EC and repealing Council Regulation (EEC) No 793/93 and Commission Regulation (EC) No 1488/94 as well as Council Directive 76/769/EEC and Commission Directives 91/155/EEC, 93/67/EEC, 93/105/EC and 2000/21/EC, including amendments.

# **SECTION 16: ADDITIONAL INFORMATION**

Full text of H- and EUH-statements:	
Acute Tox. (Inhalation)	Acute toxicity (inhale.)
Acute Tox. (Inhalation: gas)	Acute toxicity (inhalation: gas)
Aerosol	Aerosol
Carc.	Carcinogenicity
Eye Irrit.	Serious eye damage/eye irritation
Flam. Gas	Flammable gases
Press. Gas	Gases under pressure
Resp. Sens.	Resp. Sens. 1
Skin Irrit.	Skin corrosion/irritation
Skin Sens.	Sensitisation — Skin
STOT RE	Specific target organ toxicity — Repeated exposure
STOT SE	Specific target organ toxicity — Single exposure
H220	Extremely flammable gas
H222	Extremely flammable aerosol
H229	Pressurised container: May burst if heated
H315	Causes skin irritation
H317	May cause an allergic skin reaction
H319	Causes serious eye irritation
H332	Harmful if inhaled
H334	May cause allergy or asthma symptoms or breathing
	difficulties if inhaled
H335	May cause respiratory irritation
H351	Suspected of causing cancer



H373	May cause damage to organs through prolonged or repeated exposure
EUH204	Contains isocyanates. May produce an allergic reaction