

FINAL PVC ELECTRICAL TAPE

SECTION 1: IDENTIFICATIONS OF THE SUBSTANCE /MIXTURE AND OF THE COMPANY/UNDERTAKING

1.1. Product identifier

Product form : ONE COMPONENT
 Trade name : FINAL PVC ELECTRICAL TAPE
 Type of product : RUBBER ADHESIVE
 Product group : TRADE PRODUCT

1.2. Relevant identified uses of the substance or mixture and uses discouraged

Intended for general public.

1.3. Details of the supplier providing the safety data sheet

Head office: Chasbkaran Sahel Aras Co. 4th Floor, No.2, Mahan Bldg, Mojahedi Alley, Tavanir Blvd, Valiasr, Tabriz, Iran

Phone: +98 (41) 4196

info@csa-team.com

www.chasbkaran.com

1.4. Emergency telephone number

In Case Of Emergency : +98 (41) 4196

SECTION 2: HAZARDS IDENTIFICATION

Chemical Name	%	CAS No. or Note
Rubber Adhesive	8-18	
PVC resin	52-67	[9002-86-2]
Plasticizers	20-35	[117-81-7]

SECTION 3: PHYSICAL AND CHEMICAL PROPERTIES

Specific Gravity (H₂O=1) :1.25-1.45
 Softening Point :>100°C
 Decomposition Temperature :260(°C)/500o F
 Appearance and Odor :Solid appearance and with slight odor of PVC material

SECTION 4: FIRE AND EXPLOSION HAZARD DATA

Flash Point (Method Used): 320-390C (ASTM D-1929).

Extinguishing Media: water, dry chemical foam, CO₂.

Special Fire Fighting Procedures: Wear self-contained breathing apparatus and protective clothing to

prevent contact with skin and eyes.

Unusual Fire and Explosion Hazards: Any vinyl can be forced to burn by continuous application of intense Heat.

SECTION 5: HANDLING AND STORAGE

Waste Disposal Method

Use approved disposal methods as recommended by state and local agencies.

Precautions to Be Taken in Handling and Storing

Stored in cool, dry, well-ventilated area, away from flammable materials or sources of heat and flame.